



Forced-action mixers XM 2 - 650

45.297-011

When peak performance is required, professionals choose the XM



Mixing material: Reaction resin compounds, exterior insulation finishing systems, concrete (-16 mm) floor coatings, all types of mortar, screed, fillers, etc.

- Tub edge scraper with a rubber lip
- 2 tool options with different speeds
- Timer (90, 180 sec./continuous)
- Short mixing times for high hourly throughputs of material
- Items supplied: 3-piece set of mixing tools + 1 x 65 liter special mortar tub
- Trolley recommended (extra)

Technical data XM 2 - 650	
Size of mixing tub	65 Ltr.
Max. effective volume	max. 50 litres
RPM of mixing mechanism	2x120/1x630
Edge scraper speed	40 min ⁻¹
Power supply	230 V o. 400 V
Dimensions (lxwxh)	107,5x73x84,5 cm
Weight:	105 kg

Mixing Material and Recommended Vol	umes	(max. 50 L)
Material (weight without addition of water):		
	Werkzeug- _satz 1_	Werkzeug- satz 2
		() it-2 dr.
Consistency range: Very stiff to plastic		
Slightly moist concrete with grain size of -8 mm	+	-
Concrete with a max. grain size of 8	+	-
Cement screed	+	-
Synthetic resin screed	+	-
Cement Mortar	+	-
Gypsum-lime mortar	+	-
Light wall mortar	+	
Cement stucco	+	-
Gypsum plaster	+	
Loam plaster without fibers	+	-
Heat-insulating plaster	+	-
Air-entrained light exterior plaster	+	-
Mortar for natural stone slabs	+	-
2-component slab pointing mortar (-1,2 mm)	+	-
Middle-bed mortar	+	-
Tile adhesive (flex mortar)	+	-
Pointing mortar	+	-
Consistency range: soft to spreading		
Soft/spreading types of screed	+	+
Soft/spreading types of mortar	+	-
Thin-bed mortar, cement for concrete precision blocks		+
Creamy types of plaster	+	-
Adhesive grouting compounds as backing for plaster		+
Tile adhesive	+	-
Pointing mortar	+	+
Joint cements		+
Adhesive grouting compounds as backing for panels/tiles		+
2-component sealing grouting compounds	-	+
Leveling compounds	-	+
2-component epoxy-resin and sand mix	+	-
Heat-insulating cement	+	-
High-performance mortar (Flowstone)	+	-
Plastic-modified mortar systems (PCC/ECC)	+	
Steel fiber mortar	+	-
+= suitable	-= unsu	itable







QR-Code: Application video

